

IKA LIGHT WEIGHT HAMMER IN FIXINGS FOR CONCRETE, STONE, BRICK & BLOCK



Product Information



Typical applications

- Fixing stud battens to walls before cladding.
- Fixing long runs of shelf supports.
- Fixing skirting boards.

DESCRIPTION

For fast, repetitive fixing with minimal use of screwdriver required.

Suitable for use in:

- Concrete
- Stone
- Brickwork
- Blockwork

Features

1. Heat treated screw facilitates high knock-in loads with the added benefit of plug neck grip.
2. Hammer in drive screw for fast installation.
3. Extended expansion zone gives extra grip.

Hammer-In Fixing

Drill Size	Size	Max Fixture Thickness	Quantity Per Box
5	5 x 30	5 mm	100
5	5 x 40	15 mm	100
5	5 x 50	25 mm	100

6	6 x 40	15 mm	100
6	6 x 60	35 mm	100
6	6 x 70	45 mm	100
6	6 x 80	55 mm	100

8	8 x 60	25 mm	50
8	8 x 80	45 mm	50
8	8 x 100	60 mm	50
8	8 x 120	80 mm	50
8	8 x 135	90 mm	50

10	10 x 100	60 mm	25
10	10 x 135	90 mm	25

Hammer-In Fixing Performance Data

RECOMMENDED WORKING LOAD TENSION & SHEAR

	5 mm	6 mm	8 mm	10 mm
7N/mm ² Blockwork	10 kg	20 kg	30 kg	40 kg
20N/mm ² Brick	25 kg	30 kg	45 kg	50 kg
30N/mm ² Concrete	30 kg	35 kg	50 kg	75 kg

For higher load requirements please refer to our Frame Fixings