

## Product Information



### TYPICAL APPLICATIONS

- Quick, easy fixing of timber or metal door and window frames.
- No marking out – drill straight through frame.

### DESCRIPTION

Fixing timber or metal window and door frames.

### SUITABLE FOR USE IN:

Concrete,  
Stone,  
Brickwork & Blockwork.

### FEATURES

1. Countersunk Pozi-head screw provided, suitable for use with screw caps.
2. Durable PA6 grade nylon for extended fixing life.
3. Tough nylon sleeve prevents frame distortion during tightening.
4. Anti-rotation lugs.

## FRAME FIXINGS

DESCRIPTION	SCREWHEAD TYPE (mm)	HOLE DIAMETER (mm)	MAX FIXTURE THICKNESS (mm) fx	QUANTITY	PRODUCT CODE	
					PACK	BOX
8 x 60	Countersunk Pozi 3	8	20	100		
8 x 80	Countersunk Pozi 3	8	40	100		
8 x 100	Countersunk Pozi 3	8	60	100		
10 x 80	Countersunk Pozi 4	10	30	100		
10 x 100	Countersunk Pozi 4	10	50	100		
10 x 115	Countersunk Pozi 4	10	70	100		
10 x 135	Countersunk Pozi 4	10	85	100		
10 x 160	Countersunk Pozi 4	10	110	100		

## Frame Fixing Performance Data

MATERIAL	MAX RECOMMENDED WORKING LOAD	
	TENSION	TENSION
	8 mm	10 mm
Blockwork 7 N/mm <sup>2</sup>	80 kg	100 kg
Brick 20 N/mm <sup>2</sup>	100 kg	120 kg
Concrete 30 N/mm <sup>2</sup>	125 kg	150 kg