

Product Information



Masonry Nails

Typical applications

Suitable for a wide range of fixtures into masonry including battening & boarding.

DESCRIPTION

Fast, penetrating and virtually shatterproof.

Suitable for use in:

Masonry.

Features

1. Head shape prevents hammer slide and gives a neat flush fixing.
2. Zinc plated.
3. Special heat treatment to provide required hardness.
4. Washer version for increased clamping force.
5. Point shape minimises timber splitting.

SUPERIOR GRADE EUROPEAN MANUFACTURED CONCRETE NAILS

MEDIUM PLATED CONCRETE NAILS C/SUNK HEAD

| FINISH | SIZE | QTY/BOX | WEIGHT/BOX |
|-------------|---------|---------|------------|
| BRIGHT ZINC | M3 x 25 | 100 | 0.14 Kg |
| BRIGHT ZINC | M3 x 25 | | 1 Kg |
| BRIGHT ZINC | M3 x 30 | 100 | 0.18 Kg |
| BRIGHT ZINC | M3 x 40 | 100 | 0.23 Kg |
| BRIGHT ZINC | M3 x 40 | | 1 Kg |
| BRIGHT ZINC | M3 x 50 | 100 | 0.29 Kg |
| BRIGHT ZINC | M3 x 50 | | 1 Kg |
| BRIGHT ZINC | M3 x 60 | 100 | 0.32 Kg |
| BRIGHT ZINC | M3 x 70 | 100 | 0.40 Kg |
| BRIGHT ZINC | M3 x 70 | | 1 Kg |
| BRIGHT ZINC | M3 x 80 | 100 | 0.45 Kg |



®

HEAVY PLATED CONCRETE NAILS C/SUNK HEAD

| | | | |
|-------------|------------|-----|---------|
| BRIGHT ZINC | M3.4 x 70 | 100 | 0.54 Kg |
| BRIGHT ZINC | M3.4 x 100 | 100 | 0.76 Kg |

HEAVY PLATED CONCRETE NAILS ROUND HEAD

| FINISH | SIZE | QTY/BOX | WEIGHT/BOX |
|-------------|-----------|---------|------------|
| BRIGHT ZINC | M3.4 x 25 | 100 | 0.18 Kg |
| BRIGHT ZINC | M3.4 x 30 | 100 | 0.24 Kg |
| BRIGHT ZINC | M3.4 x 40 | 100 | 0.33 Kg |
| BRIGHT ZINC | M3.4 x 50 | 100 | 0.38 Kg |



®

LIGHT PICTURE PIN / PANEL PIN PLATED CONCRETE NAILS*

| FINISH | SIZE | QTY/BOX | WEIGHT/BOX |
|------------|---------|---------|------------|
| BLUE BLACK | M2 x 20 | | 1 Kg |
| BLUE BLACK | M2 x 20 | 100 | 0.10 Kg |
| BLUE BLACK | M2 x 25 | | 1 Kg |
| BLUE BLACK | M2 x 25 | 100 | 0.13 Kg |
| BLUE BLACK | M2 x 30 | | 1 Kg |
| BLUE BLACK | M2 x 40 | | 1 Kg |
| BLUE BLACK | M2 x 50 | | 1 Kg |



®

LIGHT MICKY PINS FITTED WITH WASHERS

| | | | |
|-------------|-----------|-----|--|
| BRIGHT ZINC | M2.5 x 25 | 200 | |
|-------------|-----------|-----|--|



®



Always wear suitable eye protection to BSEN166.