

IKA DOUBLE SIDED PIPE CLAMPS FOR PIPE FIXING



Product Information

DOUBLE SIDED PIPE CLAMPS



DESCRIPTION

A pipe clamp with quicklock and M8/M10 combinut for easy installation on bigger sizes.

SUITABLE FOR USE IN:

Concrete
Brick
Wood
Steel

Clamping Range	Nut	Thickness	Width	Pcs/Ctn
12-15mm	M8	1.3mm	20mm	100
16-19mm	M8	1.3mm	20mm	100
20-23mm	M8	1.3mm	20mm	100
25-28mm	M8	1.3mm	20mm	50
32-35mm	M8	1.3mm	20mm	50
40-45mm	M8	1.3mm	20mm	50
48-52mm	M8	1.3mm	20mm	50
54-58mm	M8/M10	1.3mm	20mm	50
60-64mm	M8/M10	1.3mm	20mm	50
75-80mm	M8/M10	1.5mm	20mm	50
86-91mm	M8/M10	1.5mm	20mm	50
110-115mm	M8/M10	2.0mm	20mm	50
123-128mm	M8/M10	2.0mm	20mm	50
131-137mm	M8/M10	2.0mm	20mm	50
138-144mm	M8/M10	2.0mm	20mm	50
157-163mm	M8/M10	2.0mm	20mm	50
164-170mm	M8/M10	2.5mm	20mm	50

SPECIFICATION DATA

Material: Zinc Plated Steel 6 um
Steel Dimensions: 1.3 x 20mm
from 12-15mm clamp
to 60-64mm clamp
Steel Dimensions: 1.5 x 20mm
from 75-80mm clamp
to 86-91mm clamp
2.0 x 20mm
from 110-115mm clamp
to 164-170mm clamp

FEATURES

Factory Mutual Approval
Screws: 6 x 20mm
Welded Combinut: M8+M10
Open/Close Quicklock



DOUBLE SIDED PIPE CLAMPS (Insulated)



DESCRIPTION

A pipe clamp with quicklock and M8/M10 combinut for easy installation on bigger sizes.

SUITABLE FOR USE IN:

Concrete
Brick
Wood
Steel

Clamping Range	Nut	Thickness	Width	Pcs/Ctn
12-15mm	M8	1.3mm	20mm	100
16-19mm	M8	1.3mm	20mm	100
20-23mm	M8	1.3mm	20mm	100
25-28mm	M8	1.3mm	20mm	50
32-35mm	M8	1.3mm	20mm	50
40-45mm	M8	1.3mm	20mm	50
48-52mm	M8	1.3mm	20mm	50
54-58mm	M8/M10	1.3mm	20mm	50
60-64mm	M8/M10	1.3mm	20mm	50
75-80mm	M8/M10	1.5mm	20mm	50
86-91mm	M8/M10	1.5mm	20mm	50
110-115mm	M8/M10	2.0mm	20mm	50
123-128mm	M8/M10	2.0mm	20mm	50
131-137mm	M8/M10	2.0mm	20mm	50
138-144mm	M8/M10	2.0mm	20mm	50
157-163mm	M8/M10	2.0mm	20mm	50
164-170mm	M8/M10	2.5mm	20mm	50

SPECIFICATION DATA

Material: Zinc Plated Steel 6 um
Steel Dimensions: 1.3 x 20mm
from 12-15mm clamp
to 60-64mm clamp
Steel Dimensions: 1.5 x 20mm
from 75-80mm clamp
to 86-91mm clamp
2.0 x 20mm
from 110-115mm clamp
to 164-170mm clamp
EPDM Covering: 4mm
EPDM Hardness: 40° ± 5° Shore -A
EPDM Temperature Resistance: -40°C to 110°C

FEATURES

Factory Mutual Approval
Screws: 6 x 20mm
Welded Combinut: M8+M10
Open/Close Quicklock

