

Product Information



TYPICAL APPLICATIONS

- Rapid installation of new PVCu double glazing units.
- Secure fixings for PVCu and aluminium replacement frames.
- Fixing clips into reinforced and unreinforced PVCu frames for extra support.

DESCRIPTION

Direct mounting of PVCu window frames to solid brickwork and masonry.

SUITABLE FOR USE IN:

Concrete,
Stone,
Brickwork & Blockwork.

NB. Not suitable for hollow brickwork.

FEATURES

1. Locking tabs clip into the PVCu frame.
2. Durable PA6 nylon sleeve for extended fixing life.
3. Design prevents frame distortion when tightening.

PVCu FRAME FIXING

DESCRIPTION	HOLE DIAMETER IN STRUCTURE (mm)	HOLE DIAMETER IN FIXTURE (mm)	MAX FIXTURE THICKNESS (mm)	QUANTITY	PACK	
8 x 75	8	9	15	100		
8 x 100	8	9	35	100		
10 x 100	10	11	35	100		
10 x 120	10	11	55	100		
10 x 140	10	11	75	100		
10 x 160	10	11	95	100		

PVCu FRAME FIXING Performance Data

MATERIAL	MAXIMUM RECOMMENDED WORKING LOAD TENSION AND SHEAR	
	8 mm	10 mm
7 N/mm ² Blockwork	50 kg	70 kg
20 N/mm ² Brick	60 kg	80 kg
30 N/mm ² Concrete	100 kg	130 kg