IKA PEAR SHAPED HANGER CLAMPS FOR PIPE FIXING



Product Information

PEAR SHAPED HANGER CLAMPS



DESCRIPTION

Pear Shaped pipe clamped for the suspension of the suspension of non-insulated sprinkler piping for fire protection applications.

Clamping Range	Nut	Thickness	Width	pcs/ctn
27-28mm	M8	1.5mm	20mm	100
34-35mm	M8	1.5mm	20mm	100
42-45mm	M8	1.5mm	20mm	100
48-51mm	M8	1.5mm	20mm	50
57-64mm	M8	2.0mm	20mm	50
70-76mm	M10	2.0mm	25mm	50
83-89mm	M10	2.0mm	25mm	50
102-108mm	M10	2.0mm	25mm	50
108-114mm	M10	2.0mm	25mm	50
140mm	M12	2.0mm	25mm	25
165-168mm	M12	2.0mm	25mm	25

SUITABLE FOR USE IN:

Concrete Brick Wood Steel

SPECIFICATION DATA

Material: Zinc Plated Steel 6 um

Steel Dimentions: 1.5 x 20mm

from 27-28mm clamp to 48-51mm clamp

Steel Dimensions: 2.0 x 20mm

Only 57-64mm

Steel Dimensions: 2.0 x 25mm

from 70-76mm clamp to 165-168mm clamp

FEATURES

Factory Mutual Approval.

One-piece design allows for quick and easy installation

of sprinkler pipes.

Ideal for suspension using threaded Rod.

Simple height adjustment using the knurled nut.

Long Knurled Nut for Higher Load.

Knurled nut secured by locking hook against falling out.

